



SUPPLEMENTAL/ BID BULLETIN

BID BULLETIN NO. 01

19 June 2018

Name of Project: **Procurement of Starter Toolkits for The Implementation of Republic Act 10931 or Universal Access to Quality Tertiary Education Act (UAQTEA) For CY 2018**

Approved Budget for the Contract: **Php1,166,411,878.50**

During the pre-bid conference held on 19 June 2018 and pursuant to Section 22.5 of the Revised Implementing Rules and Regulations of Republic Act No. 9184, the following are hereby amended as follows:

LOT NO.	QUALIFICATION	ITEM	TECHNICAL SPECIFICATION
18	Automotive Body Repairing NC II	Drill	<ul style="list-style-type: none">• Hand Drill• Variable speed• 220 Volts/60 Hz, 500 Watts• Double insulated• Reversible drilling• With accessories• With plastic casing and handle
28	Construction Painting NC II	Spray Gun	<ul style="list-style-type: none">• Low Pressure• Material: Stainless Steel• Fluid nozzle: 1 mm• Air pressure required: 3.0 bar• With complete set of wrenches (spanner and hex wrench)• Aluminum cup capacity: 400 mL• Air Inlet: 1/4"
75	CNC Lathe Machine Operation NC II	Outside Micrometer Caliper	<ul style="list-style-type: none">• Satin-chrome finished frame• Stainless steel chrome plated sleeve.• Capacity 0 – 25 mm• Carbide measuring faces.• Thermal insulation for the frame.• Resolution: 0.01 mm.• Accuracy: 0.004 mm.• Ratchet friction thimble and spindle lock.• Includes wrench for adjustment.• High precision instrument, used for calibration• With plastic casing

1

LOT NO.	QUALIFICATION	ITEM	TECHNICAL SPECIFICATION
77	CNC Lathe Machine Operation NC III	Outside Micrometer Caliper	<ul style="list-style-type: none"> • LCD Digimatic • Stainless Steel material and clear laser scribing • With data retention function • Resolution – 0.001 mm • Measuring Range – 0-25 mm • Accuracy: + / 0.002 mm • Battery: LR44 1.5V • With plastic casing
86	Machining NC II	Outside Micrometer Caliper	<ul style="list-style-type: none"> • Satin-chrome finished frame • Stainless steel chrome plated sleeve. • Capacity 0 – 25 mm • Carbide measuring faces. • Thermal insulation for the frame. • Resolution: 0.01 mm. • Accuracy: 0.004 mm. • Ratchet friction thimble and spindle lock. • Includes wrench for adjustment. • High precision instrument, used for calibration • With plastic casing
87	Machining NC III	Outside Micrometer Caliper	<ul style="list-style-type: none"> • LCD Digimatic • Stainless Steel material and clear laser scribing • With data retention function • Resolution – 0.001 mm • Measuring Range – 0-25 mm • Accuracy: + / 0.002 mm • Battery: LR44 1.5V • With plastic casing

For guidance and information of all concerned.


ALVIN S. FELICIANO
 Chairperson
 Bids and Awards Committee

Received by Bidder:

Date _____